

Cavity Batten Range from James Hardie 空腔板条系列



305862

Hardie™ 20mm
Horizontal Cavity Batten 2700mm

Hardie™ 20mm
横向空腔板条 2700mm

- Designed and tested to meet E2/AS1 of the NZBC
设计和测试符合新西兰建筑规范的E2/AS1标准
- H3.1 LOSP treated
经过H3.1 LOSP处理
- Must be used for the vertical installation of Stria™ Cladding and Oblique™ Weatherboard
必须用于纵向安装的Stria™ 外墙板和Oblique™ 护墙板



405308

Hardie™ CLD™ Structural Cavity Batten 3000mm

Hardie™ CLD™
结构空腔板条 3000mm

- Low density, fibre cement structural cavity batten
低密度纤维水泥结构空腔板条
- Use for the installation of Axon™ Panel to achieve a better surface finish and a economical installation solution, when compared to timber cavity batten installation
用于安装Axon™ Panel;相较于木质空腔板条,能实现更好的效果,也是更为经济实用的解决方案



306077

Hardie™ 40mm
Structural Horizontal Cavity Batten 2700mm

Hardie™ 40mm
结构水平空腔板条 2700mm

- Designed to meet the requirements of E2 of the NZBC
设计符合新西兰建筑规范E2要求
- H3.1 LOSP treated
经过H3.1 LOSP处理
- Must be used for the vertical install of Stria™ Cladding and Oblique™ Weatherboard for nogless framing to improve wall insulation
必须用于纵向安装的Stria™ 外墙板和Oblique™ 护墙板,以增强无榫框架的墙体保温性能



Ask James Hardie™ | 0800 808 868 | jameshardie.co.nz